

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Product Use: Company Identification:

Power Bolt Heavy Duty Cleaner image supply, Inc. P.O. Box 1108 Lumberton, NC 28360

Phone Number: D.O.T. Emergency Phone: Date of Preparation: Revision Date:

Precautionary statement - Storage

Store locked up.

(910)738-1166 Chem-Tel (800)255-3924 April 9, 1996 October 5, 2014 Rev. No. 3

SAFETY DATA SHEET

POWER BOLT

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW



CORROSIVE: Causes Severe Skin Burns and eye damage

Precautionary Statement – Prevention

Wear personal protective equipment as required. Wash thoroughly after handling. Do not breathe dust or mist.

Precautionary Statement – Response

Target Organ:	Skin, eyes, gastrointestinal tract
IF ON SKIN:	Remove/Take off immediately all contaminated clothing. Rinse skin with Water
IF IN EYES:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
IF SWALLOWED:	Rinse mouth. Do NOT induce vomiting.
IF INHALED:	Remove to fresh air and deep at rest in a position comfortable for breathing.

Precautionary Statement – Disposal

Dispose of contents/container in accordance with local and national regulations.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS#	Wt. %
*Butyl cellosolve (2-Butoxyethanol)	111-76-2	Trade Secret
Sodium Metasilicate Penta	6834-92-0	Trade Secret
Sodium Hydroxoide Soluution, Caustic	1310-73-2	Trade Secret

SECTION 313 SUPPLIER NOTIFICATION

* Indicates hazardous ingredients which are toxic chemicals subject to the reporting requirements of section 313 of THE EMERGENCY PLANNING & COMMUNITY RIGHT-TO-KNOW ACT OF 1986 and of 40 CFR 372. The chemical name, CAS #, and percent by weight must be included in all SDS copied and distributed for this material.

Section 4: FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for 15 -20 minutes, seek medical attention.
Skin Contact:	Immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Call a physician if irritation develops and persists.
Inhalation:	If difficulty or discomfort in breathing is experienced, remove to fresh air and get medical attention.
Ingestion:	Harmful or fatal if swallowed. Give several glasses of water followed by citrus juice or vinegar. Get medical attention.

Section 5: FIRE FIGHTING MEASURES

Flammability:	Not flammable by WHMIS/OSHA criteria
Means of Extinction:	
Suitable Extinguishing Media:	Powder, water spray, foam, carbon dioxide.
Products of Combustion:	None
Explosion Data:	
Sensitivity to Mechanical Impact:	Not Available.
Sensitivity of Static Discharge:	Not Available.
Protection of Firefighters:	Containers may explode when heated. Keep up wind of fire. Wear full fire fighting turn-out gear (full Bunker
	gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Use personal protection recommended in Section 8. Isolate the hazard area and Deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.	
Environmental Precautions:		
Methods for Containment:	Absorb large spills with floor dry material (see disposal below). Small spills: Flush with water and pick up with mop or wet vacuum.	
Waste Disposal Method:	Dispose of in accordance with state or local regulations. EPA Hazardous Waste Classification: Corrosive ($pH = 13$ on concentrate). Do not dispose of in storm drains or streams.	

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. When using, do not eat or drink. Wash hands before eating, drinking, or smoking. Storage:

OSHA-PEL

50 PPM

2 mg/m3

N/A

Keep out of the reach of children. Keep from freezing. Keep container closed. Do not pressure container to close.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Engineering Controls:

Ingredient Butyl cellosolve (2-Butoxyethanol) Sodium Metasilicate Penta Sodium Hydroxide, Caustic

Porsonal Protective Equipment:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

ACGIH-TLV

20 PPM

N/A

N/A

reisonal riotecuve Equipment.	
Eye/Face Protection:	Wear eye/face protection. Goggles
Hand Protection:	Alkali Resistant Gloves
Skin and Body Protection:	Wear suitable protective clothing.
Respiratory Protection:	Ventilate to keep air below TLV. A NIOSH approved respirator for organic vapor should be worn if
	needed to keep level below TLV.
General Hygiene Consideration:	Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 212 Degrees F Volatile: (% by Volume, 80%) Evaporation Rate: N/A Solubility in Water: Complete 13.1-13.3 Appearance and Odor: Thin Green liquid-butyl odor

Section 10: STABILITY AND REACTIVITY

Stability:	Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.
Conditions of Reactivity: Incompatible Materials:	Heat. Incompatible materials. Acids, Ammonium salts, Amines, Activated Carbon, Cyanides, Reducers, Zinc. May react with Secondary/Tertiary Amines to form Nitrosamines.
Hazardous Decompositions Products: Possibility of Hazardous Reactions:	May include, and are not limited to: Carbondioxide, Carbonmonocide, Oxides of Nitrogen No dangerous reaction known under conditions of normal use.

Spec. Gravity: (Water=1): 1.05

Vapor Density: Same as Water

Approx. Product Weight: 10 LBS/GAL

Melting Point: N/A

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE Component Analysis		
Ingredients	LD50 (irak)	LC50
Butyl cellosolve (2-Butoxyethanol)	Not Available	Not Available
Sodium Metasilicate Penta	Not Available	Not Available
Sodium Hydroxide, Caustie	Not Available	Not Available

Eye:	Direct Contact of product with eyes can cause severe irritation and damage.
Skin:	Prolonged or repeated contact of product with skin may cause irritation.
Ingestion:	Not a normal route of exposure. May cause burns. Harmful: may cause lung damage if swallowed.
Inhalation:	Product spray mist or fog may cause irritation to nose, throat and lungs if adequate ventilation is not employed.

EFFECTS OF CHRONIC EXPOSURE

Chronic Effects:Existing Dermatitis may be aggravated by exposure.Carcinogenicity:Not hazardous by WHMIS/OSHA criteria.

Ingredient	Chemical Listed as Carcinogen or
	Potential Carcinogen*
Sodium Metasilicate Penta	Not Listed
Butyl cellusolve	Not Listed
Mutagenicity:	Not hazardous by WHMIS/OSHA criteria.
Reproductive Effects:	Not hazardous by WHMIS/OSHA criteria.
Developmental Effects:	
Teratogenicity:	Not hazardous by WHMIS/OSHA criteria.
Embryotoxicity:	Not hazardous by WHMIS/OSHA criteria.
Respiratory Sensitization:	Not hazardous by WHMIS/OSHA criteria.
Skin Sensitization:	Not hazardous by WHMIS/OSHA criteria.
Toxicologically Synergistic Materials:	Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Persistence / Degradability: Bioaccumulation / Accumulation: Mobility in Environment: May cause long-term adverse effects in the aquatic environment. Not available. Not available. Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

Applicable regulations: 49 CFR = yes; IMCO = no; IATA = no Proper shipping name: Sodium hydroxide Hazardous waste characteristics: Ignitability = not applicable; Corrosivity = yes; Reactivity = not applicable

DOT Classification:

Compounds, Cleaning Liquid (contains Sodium Hydroxide),8, UN1824, PG II

Section 15: REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD:

Unless otherwise specified in Section 3 of this document, this product is not and does not contain any "Hazardous Chemicals", as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Section 16: OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy and completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that they are the only hazards that exist.